



PacketV® STB A140

High Definition (HD) IPTV Set Top Box (STB)

Specifications

| | |
|------------------------------|---|
| SIZE AND WEIGHT | 114mm x 100mm x 35mm. 280g (excluding accessories and packaging) |
| INPUTS | Ethernet 10/100 BaseT via RJ-45 shielded connector |
| OUTPUTS | HDMI 1.3a. (excl. Deep colour and DTS audio) with HDCP. S/PDIF (optical). USB2.0. 10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio. RF Mod and loop through. |
| POWER | 5V DC at 1.5A via external power supply Less than 8W typical usage (external supply input voltage 100-240V AC 50-60Hz, 0.8A max, output 5VDC 3A) |
| CODECS | MPEG-2 MP@HL. MPEG-4 pt10 AVC/H.264 HP@L4 |
| VIDEO RESOLUTIONS | Decodes up to 720p and 1080i. Displays up to 1080p |
| GRAPHICS RESOLUTIONS | HD graphics up to 1280x720 |
| AUDIO | Stereo audio and Dolby 5.1 surround via S-PDIF and HDMI. Dolby Digital+ pass through to external decoder |
| SECURITY | Wide selection of DRM and Conditional Access support. Macrovision (optional), CGMS-A |
| MEMORY | 128MB Flash, 256MB RAM |
| FRONT PANEL LEDS | Power on/IR command received (Red) |
| OPERATING ENVIRONMENT | ETS 300-019-1-3 Class 3.1 |
| EMC CONFORMANCE | FCC Part 15 class B. 2004/108/EC EN55022 |
| SAFETY APPROVALS | CAN/ CSA-C22.2 No. 60950-1-03. EN60950 |
| ROHS | 2002-95-EC |
| WEEE | 2002-96-EC |
| OPERATING TEMPERATURE | 0°C (32°F) to 40°C (104°F) |
| STORAGE HUMIDITY | 5% to 95% RH (non-condensing) |
| STANDARD ACCESSORIES | Remote control (510-710) Power supply with regional power cord Anti-slip base |

