



PacketTV® STB H140

High Definition (HD) IPTV Set Top Box (STB)
in a Mountable Enclosure

Specifications

| | |
|------------------------------|---|
| SIZE AND WEIGHT | 140mm x 114mm x 40mm. 320g (excluding accessories and packaging) |
| INPUTS | 1 x Ethernet 10/100 BaseT via RJ-45 shielded connector |
| OUTPUTS | HDMI 1.3a. with HDCP and CEC 10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio. S/PDIF (optical). 2x USB2.0. RS232 serial connector |
| POWER | 5V DC at 1.5A via external power supply Less than 8W typical usage (external supply input voltage 100-240V AC 50-60Hz 3A max) |
| CODECS | MPEG-2 MP@HL.MPEG-4 pt10 AVC/H.264 HP@L4 |
| VIDEO RESOLUTIONS | Decodes up to 720p and 1080i. Displays up to 1080p |
| GRAPHICS RESOLUTIONS | HD graphics up to 1280x720 |
| AUDIO | Analogue stereo audio out.Stereo and Dolby 5.1 surround via S-PDIF and HDMI. Dolby Digital+ pass through to external decoder |
| SECURITY | Wide selection of DRM and Conditional Access support. HDCP on HDMI Macrovision on SD outputs (option) |
| MEMORY | 128MB Flash, 256MB RAM |
| FRONT PANEL LEDS | Power on/IR command received (Red) |
| OPERATING ENVIRONMENT | ETS 300-019-1-3 Class 3.1 |
| EMC CONFORMANCE | FCC Part 15 class B. 2004/108/EC EN55022 |
| SAFETY APPROVALS | CAN/ CSA-C22.2 No. 60950-1-03. EN60950 |
| ROHS | 2002-95-EC |
| WEEE | 2002-96-EC |
| OPERATING TEMPERATURE | 0°C (32°F) to 40°C (104°F) |
| STORAGE HUMIDITY | 5% to 95% RH (non-condensing) |
| STANDARD ACCESSORIES | Remote control (510-710) Power supply with regional power cord |

